Vehicle Weight and Dimension (VW&D) Reforms

Ontario Ministry of Transportation



Task Force on VW&D Policy
November 2005

VW&D Reforms - 4 Phases

Phase 1 (2001) - 'light' semi-trailers

Phase 2 (2002) - dump semi-trailers

Phase 3 (2005) - 'heavy' semi-trailers / doubles

Phase 4 (2008) - straight trucks and trailers

Migration to SPIF

- From 'permissive' system
- To prescribed vehicles that are:

Safe
Productive
Infrastructure-Friendly

SPIF

3

Requirement to be SPIF

	Must be SPIF as of:	Consequence of non-SPIF:
Long Combinations	Always	Illegal
Dump Semi-Trailers	Any trailer built in or after 2003	4500 / 9000 kg penalty
Light (1,2,3 axles) Semi-Trailers	Effective January 1, 2006	3000 kg penalty (will increase to 4500 kg)
Heavy (4+ axles) Semis / Doubles	Any trailer built in or after 2006	4500 / 9000 kg penalty

SPIF Dimensional Limits

- Tractor wheelbase max 6.2m (244")
 (if long comb or tractor built after 2005)
- Semi-trailer length max 16.2m (53')
- Semi-trailer wheelbase max 12.5m (41')
- Effective rear overhang 35% of w/b
- Track width 2.5 to 2.6m (98" to 102")

5


General SPIF Requirements


- · 'Invisible' lift-axles are allowed.
- Single tires allowed 8,000 kg / fixed axle.
- Front axle capped at 7,700 kg.
- On-board scale required (4, 5 and 6 axle semi-trailers only).
- Enhanced braking system (5 and 6 axle semi-trailers only).


SPIF Self-Steers


- · Self-steers can be liftable.
- · Restrictions on lift-controls.
- Self-steers must load-equalize to within 500 kg of average on fixed axles.
- Single tires allowed on self-steer axles up to 8,500 kg on quad and 9,000 kg on triaxle.


7











VW&D Reforms

Highway Traffic Act Regulation 413/05

www.e-laws.gov.on.ca

13

MTO Contact (VW&D)

Ron Madill
Project Lead - VW&D Reforms
(519) 473-6543

ron.madill@mto.gov.on.ca